



# CXone Mpower EXPERT

## NIC 端口在 IFstat 中看到 CRC 错误

[https://kb-cn-stage.netapp.com/on-prem/ontap/OHW/OHW-KBs/NIC\\_port\\_seeing\\_CRC\\_errors\\_in\\_ifstat](https://kb-cn-stage.netapp.com/on-prem/ontap/OHW/OHW-KBs/NIC_port_seeing_CRC_errors_in_ifstat)

Updated: Wed, 22 Apr 2026 07:16:17 GMT

### 适用场景

- FAS / AFF 系统
- 网络适配器

### 问题描述

- ifstat 命令的输出显示 受影响端口上存在较高的CRC错误

```
::> system node run -node <NODE_NAME> -command ifstat <PORT>
```

```
-- interface e4a (7 hours, 33 minutes, 13 seconds) --
```

#### RECEIVE

Total frames:	10739k		Frames/second:	395		Total bytes:	14537m
Bytes/second:	534k		Total errors:	4921		Errors/minute:	11
Total discards:	0		Discards/minute:	0		Multi/broadcast:	334k

'NetApp provides no representations or warranties regarding the accuracy or reliability or serviceability of any information or recommendations provided in this publication or with respect to any results that may be obtained by the use of the information or observance of any recommendations provided herein. The information in this document is distributed AS IS and the use of this information or the implementation of any recommendations or techniques herein is a customers responsibility and depends on the customers ability to evaluate and integrate them into the customers operational environment. This document and the information

```
Non-primary u/c:    0 | CRC errors:    4921 | Runt frames:    0
Fragment:         0 | Long frames:    0 | Jabber:        0
```

- 事件日志中报告了以下错误：

```
[Node-02: vifmgr: vifmgr.cluscheck.crcerrors:alert]: Port e4a on node Node-02
is reporting a high number of observed CRC errors.
```