



"sysconfig-a " 将 "failed" 显示为 Flash Cache 状态

https://kb-cn-stage.netapp.com/on-prem/ontap/OHW/OHW-KBs/sysconfig_a_shows_Failed_as_Flash_...

Updated: Wed, 22 Apr 2026 03:46:36 GMT

适用于

- FAS3220
- Data ONTAP 8.

问题

- ""sysconfig -a 将 "" 显示Failed为 Flash Cache 状态。

示例：

```
slot 2: Flash Cache 2 (512 GB)
State: Failed
Model Name: X1973A-R6
Serial Number: 9458198419
Part Number: 111-00902
```

Board Revision: D0

- EMS 日志报告“`iomem.card.fail.internal:critical`”和“`fmm.domain.card.failure:error`”。

示例：

```
[?] Sun Feb 23 20:46:52 JST [node_name: iomem.card.fail.internal:critical]:  
Caching module (model name X1973A-R6, serial number 9458198419, part number  
111-00902) in slot 2 has experienced a fatal internal error (0x4007) and is  
being taken offline.
```

```
[?] Sun Feb 23 20:46:52 JST [node_name: fmm_main:  
fmm.domain.card.failure:error]: Flash Cache in slot 2 (model name X1973A-  
R6, serial number 9458198419, part number 111-00902): Flash device failed  
and needs to be updated or repaired or replaced.
```