



## DS4246何时需要四个PSU

[https://kb-cn-stage.netapp.com/on-prem/ontap/OHW/OHW-KBs/When\\_does\\_DS4246\\_need\\_four\\_PSUs](https://kb-cn-stage.netapp.com/on-prem/ontap/OHW/OHW-KBs/When_does_DS4246_need_four_PSUs)

Updated: Wed, 22 Apr 2026 08:47:56 GMT

### 适用场景

- DS4243
- DS4246

### 问题解答

- 使用SSD或7.2k磁盘时、需要2个PSU + 2个插槽挡片。
- 使用10k或15k磁盘时、需要4个PSU。

### 追加信息

请参阅

[1]第44页的《DS4243、DS2246、DS4486和DS4246安装和服务指南》。

#### **DS4243磁盘架附带的电源数量**

DS4243磁盘架中使用的磁盘驱动器类型决定了确保适当冷却、通风和供电所需的电源数量。

- 如果DS4243磁盘架包含固态硬盘(SSD)、或者磁盘驱动器的转速低于10、000 RPM、则需要两个电源和两个电源挡片来

'NetApp provides no representations or warranties regarding the accuracy or reliability or serviceability of any information or recommendations provided in this publication or with respect to any results that may be obtained by the use of the information or observance of any recommendations provided herein. The information in this document is distributed AS IS and the use of this information or the implementation of any recommendations or techniques herein is a customers responsibility and depends on the customers ability to evaluate and integrate them into the customers operational environment. This document and the information

填充磁盘架中的四个电源托架。这些磁盘架需要两个电源插座。

- 如果DS4243磁盘架的磁盘驱动器转速为10、000 RPM或更快(通常为SAS磁盘驱动器)、则磁盘架需要四个电源。这些磁盘架需要四个电源插座。