



数据SVM是否可用于BGP对等？

https://kb-cn-stage.netapp.com/on-prem/ontap/da/NAS/NAS-KBs/Can_data_SVMs_be_used_for_BGP...

Updated: Wed, 22 Apr 2026 04:09:18 GMT

适用场景

- ONTAP 9
- BGP

问题解答

- 需要在system-sVM上创建BGP LIF
- 使用默认IP空间、可以在cluster-SVM上创建BGP LIF
- 使用新的IP空间需要system-sVM
- 此命令将显示Vserver类型及其IP空间

```
::> vserver show -fields type,ipSPACE
vserver  type  ipSPACE
-----  ----  -----
cluster1 admin Default
```

'NetApp provides no representations or warranties regarding the accuracy or reliability or serviceability of any information or recommendations provided in this publication or with respect to any results that may be obtained by the use of the information or observance of any recommendations provided herein. The information in this document is distributed AS IS and the use of this information or the implementation of any recommendations or techniques herein is a customers responsibility and depends on the customers ability to evaluate and integrate them into the customers operational environment. This document and the information

```
cluster1-01
    node -
cluster1-02
    node -
svm1_cluster1
    data Default
svm2_cluster1
    data Default
```

追加信息

- [设置边界网关协议\(BGP\)](#)
- [SVM的类型](#)