



"CIFS domain s发现-server show/reset-server"命令超时

https://kb-cn-stage.netapp.com/on-prem/ontap/da/NAS/NAS-KBs/cifs_domain_discovered-servers_sho...

Updated: Wed, 22 Apr 2026 04:07:09 GMT

适用场景

- ONTAP 9
- CIFS/SMB
- 域控制器发现

问题描述

- 无法显示或清除已发现域服务器的列表
- 显示或重置SVM的已发现域控制器列表的命令失败、并显示 超时错误

示例：

```
Cluster::> cifs domain discovered-servers show
Warning: Unable to list entries on node cluster-01. Timeout: Operation
"cifs_domain_discovered_server_byname_iterator::next_imp()" took longer than 25
```

```
seconds to complete [from mgwd on node "cluster-01" (VSID: -1) to mgwd  
at 10.11.12.13]
```

```
Cluster::> vserver active-directory discovered-servers reset-servers  
Error: command failed: The command to re-discover servers failed on Vserver  
SVM. Reason: RPC: Timed out.
```

- 在域发现过程中、EMS日志还会每4小时显示一次LDAP错误消息

```
Thu May 28 04:16:48 UTC [Cluster_01: secd: secd.ldap.noServers:EMERGENCY]: None  
of the LDAP servers configured for Vserver (SVM_TEST) are currently accessible  
via the network for LDAP service type (Service: LDAP (Active Directory),  
Operation: SiteDiscovery).
```