



CVE-1999-1225是否会影响ONTAP？

https://kb-cn-stage.netapp.com/on-prem/ontap/da/NAS/NAS-KBs/Does_CVE-1999-1225_affect_ONTAP

Updated: Wed, 22 Apr 2026 11:40:12 GMT

适用场景

ONTAP 9

问题解答

根据 [RFC 1813](#)，ONTAP 9会使用所需的mountstat3代码进行响应。

- 对于不存在的目录：

```
# mount nfs1:/test /t
mount.nfs: mounting nfs1:/test failed, reason given by server: No such file or
directory
```

- 对于已存在但用户 无权访问的目录：

```
# mount nfs1:/test2 /t
```

'NetApp provides no representations or warranties regarding the accuracy or reliability or serviceability of any information or recommendations provided in this publication or with respect to any results that may be obtained by the use of the information or observance of any recommendations provided herein. The information in this document is distributed AS IS and the use of this information or the implementation of any recommendations or techniques herein is a customers responsibility and depends on the customers ability to evaluate and integrate them into the customers operational environment. This document and the information

```
mount.nfs: access denied by server while mounting nfs1:/test2
```

注意：如上所述(将导出到状态为只读(ro)的所有主机)、可以确定给定的导出目录是否存在。

- 撤消对/的ro访问后、响应如下所示：

```
# mount nfs1:/test /t
mount.nfs: access denied by server while mounting nfs1:/test
```

注意：在此配置中、ONTAP不再向未经授权的用户确认是否存在挂载点。必须为新挂载和现有挂载设置此值。

追加信息

[CVE-1999-1225 \(mitre.org\)](https://www.mitre.org/cve/1999/1225)