



CXone Mpower EXPERT

是否可以从Vscan中排除读取操作？

https://kb-cn-stage.netapp.com/on-prem/ontap/da/NAS/NAS-KBs/Is_it_possible_to_exclude_read_oper...

Updated: Wed, 22 Apr 2026 07:32:36 GMT

适用场景

- ONTAP 9
- CIFS
- vscan

问题解答

- 可以使用 Vscan文件操作配置文件在CIFS共享级别控制触发请求的操作
- 默认Vscan文件操作配置文件为 `standard`，和 `opencloserename` 操作可以触发病毒扫描。

示例

```
::> vserver cifs share modify -vserver svml -share-name share1 -vscan-fileop-profile standard
```

```
[-vscan-fileop-profile {no-scan|standard|strict|writes-only}] - Vscan File-
```

'NetApp provides no representations or warranties regarding the accuracy or reliability or serviceability of any information or recommendations provided in this publication or with respect to any results that may be obtained by the use of the information or observance of any recommendations provided herein. The information in this document is distributed AS IS and the use of this information or the implementation of any recommendations or techniques herein is a customers responsibility and depends on the customers ability to evaluate and integrate them into the customers operational environment. This document and the information

Operations Profile

This optional parameter controls which operations trigger virus scans. The value can be one of the following:

- o no-scan: Virus scans are never triggered for this share.
- o standard: Virus scans can be triggered by open, close, and rename operations. This is the default profile.
- o strict: Virus scans can be triggered by open, read, close, and rename operations.
- o writes-only: Virus scans can be triggered only when a file that has been modified is closed.

追加信息

附加信息_text