



由于无法访问LDAP服务器、出现secd.keros.preauth"错误

https://kb-cn-stage.netapp.com/on-prem/ontap/da/NAS/NAS-KBs/secd.kerberos.preauth_errors_due_to...

Updated: Wed, 22 Apr 2026 07:30:09 GMT

适用场景

- ONTAP 9
- LDAP 客户端

问题描述

- EMS中的警告事件

```
secd.kerberos.preauth: A Kerberos pre-authentication failure occurred for SVM "svm1" due to invalid credentials for SVM1$@DOMAIN.LOCAL.
```

```
secd.conn.auth.failure: Vserver (svm1) could not authenticate over the network to server (ldap01). Error: Can't contact LDAP server (Service: LDAP (NIS & Name Mapping), Operation: Check LDAP Config).
```

- SecD日志

'NetApp provides no representations or warranties regarding the accuracy or reliability or serviceability of any information or recommendations provided in this publication or with respect to any results that may be obtained by the use of the information or observance of any recommendations provided herein. The information in this document is distributed AS IS and the use of this information or the implementation of any recommendations or techniques herein is a customers responsibility and depends on the customers ability to evaluate and integrate them into the customers operational environment. This document and the information

```
info : TCP connection to ip 10.20.30.122, port 636 failed: Connection refused.  
{ in _connect() at src/connection_manager/secd_connection_shim.cpp:594 }
```

- 数据包跟踪

```
10.20.30.123 → 10.20.30.122 TCP 74 60655 → 636 [SYN] Seq=0 Win=65535 Len=0  
MSS=1460 WS=256 SACK_PERM TSval=1868178423 TSecr=0  
10.20.30.122 → 10.20.30.123 TCP 54 636 → 60655 [RST, ACK] Seq=1 Ack=1 Win=0  
Len=0
```