



---

## 正在记录 `secd.kerberos.preauth` 事件

[https://kb-cn-stage.netapp.com/on-prem/ontap/da/NAS/NAS-KBs/secd.kerberos.preauth\\_event\\_is\\_bein...](https://kb-cn-stage.netapp.com/on-prem/ontap/da/NAS/NAS-KBs/secd.kerberos.preauth_event_is_bein...)

Updated: Wed, 22 Apr 2026 03:59:31 GMT

### 适用场景

- ONTAP 9
- NFS
- Kerberos

### 问题描述

经常记录 `secd.kerberos.preauth` 事件

```
Wed Jun 23 06:25:30 +0200 [node-01: secd: secd.kerberos.preauth:error]: Kerberos pre-authentication failure due to out-of-sync machine account password for vserver (vserver1). Wed Jun 23 08:09:43 +0200 [node-01: secd: secd.kerberos.preauth:error]: Kerberos pre-authentication failure due to out-of-sync machine account password for vserver (vserver1). Wed Jun 23 09:02:05 +0200 [node-01: secd: secd.kerberos.preauth:error]: Kerberos pre-authentication failure due to out-of-sync machine account password for vserver (vserver1). Wed Jun 23 09:30:31 +0200 [node-01: secd: secd.kerberos.preauth:error]: Kerberos pre-authentication failure due to out-of-sync machine account password for vserver (vserver1). Wed Jun 23 10:03:50 +0200 [node-01: secd: secd.kerberos.preauth:error]: Kerberos pre-authentication failure due to out-of-sync machine account password
```

---

'NetApp provides no representations or warranties regarding the accuracy or reliability or serviceability of any information or recommendations provided in this publication or with respect to any results that may be obtained by the use of the information or observance of any recommendations provided herein. The information in this document is distributed AS IS and the use of this information or the implementation of any recommendations or techniques herein is a customers responsibility and depends on the customers ability to evaluate and integrate them into the customers operational environment. This document and the information

for vserver (vserver1).

- 最终用户不会报告任何功能问题
- Kerberos 身份验证失败并导致 `secd.kerberos.preauth` 事件
- 此后尝试使用 NTLM 身份验证成功，这会使客户无法识别并受到影响