



---

## 可以停止wafllron

[https://kb-cn-stage.netapp.com/on-prem/ontap/Ontap\\_OS/OS-KBs/Can\\_wafllron\\_be\\_stopped](https://kb-cn-stage.netapp.com/on-prem/ontap/Ontap_OS/OS-KBs/Can_wafllron_be_stopped)

Updated: Wed, 22 Apr 2026 08:46:15 GMT

### 适用场景

- ONTAP 9

### 问题解答

**警告：** 除非 [NetApp 技术支持指示](#)，否则决不能停止Wafllron。

可以停止wafllron。使用以下命令：

```
::> set diagnostic  
::*> storage aggregate wafllron stop -aggregate aggr1
```

```
WARNING: The current status of wafllron on aggregate aggr1 is 'starting'. Do  
you still want to continue? {y|n}:
```

---

'NetApp provides no representations or warranties regarding the accuracy or reliability or serviceability of any information or recommendations provided in this publication or with respect to any results that may be obtained by the use of the information or observance of any recommendations provided herein. The information in this document is distributed AS IS and the use of this information or the implementation of any recommendations or techniques herein is a customers responsibility and depends on the customers ability to evaluate and integrate them into the customers operational environment. This document and the information

如果Wafllron已停止、则需要使用 `storage aggregate waflliron start` 命令重新启动它。

如果Wafllron停机在：

- 阶段1 (挂载)、则必须从头开始。
- 在第2或第3阶段、提交到重新启动点的任何更改都将保留、但是、Wafllron将在运行 `waflliron start` 命令后在第1阶段再次开始扫描。

## 追加信息

其他信息文本