



MetroCluster：由于聚合快照、无法对NAE聚合进行解密

https://kb-cn-stage.netapp.com/on-prem/ontap/Ontap_OS/OS-KBs/MetroCluster__cannot_decrypt_NA...

Updated: Wed, 22 Apr 2026 07:31:24 GMT

适用场景

- ONTAP 9
- MetroCluster (MCC)
- NetApp 聚合加密 (NAE)

问题描述

- 无法将NAE聚合转换为纯文本。

```
Cluster::*> storage aggregate modify -aggregate aggr1 -force-disable-encrypt-  
with-aggr-key true -encrypt-with-aggr-key false
```

```
Warning: Aggregate "aggr1" has aggregate Snapshot copy which might contain NAE  
(NetApp Aggregate Encryption) volume. Ensure that there is no NAE volume in the  
aggregate Snapshot copy before disabling NAE.
```

'NetApp provides no representations or warranties regarding the accuracy or reliability or serviceability of any information or recommendations provided in this publication or with respect to any results that may be obtained by the use of the information or observance of any recommendations provided herein. The information in this document is distributed AS IS and the use of this information or the implementation of any recommendations or techniques herein is a customers responsibility and depends on the customers ability to evaluate and integrate them into the customers operational environment. This document and the information

```
Do you want to continue? {y|n}: y
```

- 聚合中无卷。

```
Cluster::*> volume show -aggregate aggr1  
There are no entries matching your query.
```

```
Cluster::*> vol show -aggregate aggr2  
There are no entries matching your query.
```

- 由于SyncMirror (应为MCC)、AGG会发生快照。

```
::> node run -node node1 snap list -A
```

```
Aggregate aggr0  
working...
```

%/used	%/total	date	name
0% (0%)	0% (0%)	Oct 29 17:54	mirror_resync.1029175419 (node1) (busy, syncmirror)

```
Aggregate aggr1  
working...
```

%/used	%/total	date	name
0% (0%)	0% (0%)	Oct 29 17:55	mirror_resync.1029175522 (node1) (busy, syncmirror)

```
Aggregate aggr2  
working...
```

%/used	%/total	date	name
0% (0%)	0% (0%)	Oct 29 17:57	mirror_resync.1029175735 (node1) (busy, syncmirror)