



ONTAP升级后报告SwitchIfInBandac用量_警报

https://kb-cn-stage.netapp.com/on-prem/Switches/General_Kbs/ONTAP_reporting_SwitchIfInBandwidt...

Updated: Wed, 22 Apr 2026 03:44:40 GMT

适用场景

- ONTAP 9
- FAS/AFA系统
- BES-53248集群交换机

问题描述

- ONTAP升级后、系统会报告并清除以下SwitchIfInBandac用量_Alert事件：

```
[node1: cshmd: hm.alert.raised:alert]: Alert Id = SwitchIfInBandwidth_Alert ,  
Alerting Resource = Cluster-sw2/Slot: 0 Port: 1 25G - Level raised by monitor  
ethernet-switch
```

```
[node1: cshmd: hm.alert.cleared:notice]: Alert Id = SwitchIfInBandwidth_Alert ,  
Alerting Resource = Cluster-sw2/Slot: 0 Port: 1 25G - Level cleared by monitor  
ethernet-switch
```

'NetApp provides no representations or warranties regarding the accuracy or reliability or serviceability of any information or recommendations provided in this publication or with respect to any results that may be obtained by the use of the information or observance of any recommendations provided herein. The information in this document is distributed AS IS and the use of this information or the implementation of any recommendations or techniques herein is a customers responsibility and depends on the customers ability to evaluate and integrate them into the customers operational environment. This document and the information

- 交换机日志指示所报告端口的利用率正常。