



如何在ONTAP 中启用SnapDiff

https://kb-cn-stage.netapp.com/on-prem/ontap/dp/SnapDiff/SnapDiff-KBs/How_to_enable_SnapDiff_in...

Updated: Wed, 22 Apr 2026 07:46:48 GMT

适用场景

- ONTAP 9
- SnapDiff

问题描述

本知识库文章概述了在ONTAP 中启用SnapDiff (v1、v2和v3)的操作步骤

操作步骤

Snap 差异 版本	操作步骤
Snap 差异v1	默认情况下、ONTAP中会启用Snap 差异v1、不需要运行任何命令即可启用

'NetApp provides no representations or warranties regarding the accuracy or reliability or serviceability of any information or recommendations provided in this publication or with respect to any results that may be obtained by the use of the information or observance of any recommendations provided herein. The information in this document is distributed AS IS and the use of this information or the implementation of any recommendations or techniques herein is a customers responsibility and depends on the customers ability to evaluate and integrate them into the customers operational environment. This document and the information

1. 运行以下命令以启用

```
::> set adv  
::> vserver snapdiff-rpc-server on -vserver <svm_name>
```

Snap差异v2

2. 以进行验证

```
::> set adv  
::> vserver snapdiff-rpc-server show
```

1. 运行以下命令以启用

```
::> set adv  
::> vserver snapdiff-rpc-server on -vserver <svm_name>
```

Snap差异v3

2. 以进行验证

```
::> set adv  
::> vserver snapdiff-rpc-server show
```

追加信息

附加信息_text